










BAYFIELD[®]

RETAINING WALL SYSTEM

DISTRESSED FACE ADAPTABLE TO
 MANY DIFFERENT LANDSCAPES

SHAPES & SIZES

	Dimensions* H x W x D (in)	Weight* (lbs)	Coverage (sqft)
LARGE WALL UNIT			
	6 x 18 x 10	59	0.75
MEDIUM WALL UNIT			
	6 x 12 x 10	43	0.50
SMALL WALL UNIT			
	6 x 6 x 10	21	0.25
CORNER/COLUMN			
	6 x 18 x 9	75	1.13
SHORTCUT[®] CAP			
	3 x 8/7 x 13	22	0.63
STEP			
	6 x 16 x 12	89	
TORPEDO[™] BASE BLOCK			
	4 x 15 ³ / ₄ x 11	47	1.31

FEATURES & BENEFITS

- Can be used for gravity walls up to 3 feet 6 inches high, including buried course, but excluding the cap*
- Original rear-lip block makes installation easy
- Taller walls can be built using geosynthetic reinforcement or the Anchorplex[™] retaining wall system when designed by a qualified engineer
- Minimum outside radius, measured on the top course to the front of the units: 3 feet**
- Minimum inside radius, measured on the base course to the front of the units: 6 feet.**
- Setback/System Batter 11/8" / 10.6 degrees

*The maximum gravity wall height is project specific and may be lower than this height.

**May vary depending on the installation pattern.

