










BELAIR[®] 2.0

RETAINING WALL SYSTEM

THE APPEARANCE OF HAND-WORKED STONE PROVIDES A TIMELESS DISTINCTION TO ANY OUTDOOR SPACE.

SHAPES & SIZES

WALL UNIT	Dimensions* H x W x D (in)	Weight* (lbs)	Coverage (sqft)
 LARGE WALL UNIT	6 x 16 x 8	52	0.67
 LARGE WALL UNIT	6 x 16 x 8	52	0.67
 MEDIUM WALL UNIT	6 x 10 x 8	32	0.42
 SMALL WALL UNIT	6 x 6 x 8	21	0.25
 TORPEDO™ BASE BLOCK	4 x 15 ³ / ₄ x 11	47	1.31
 DOUBLE SIDED CAP	3 x 8 ⁷ / ₇ x 13 ¹ / ₂	22	0.63
 END CAP	3 x 8 x 13 ¹ / ₂	21	0.67
 CORNER/COLUMN	6 x 16 ³ / ₄ x 8	57	
 WALL END	6 x 11 x 8	36	

FEATURES & BENEFITS

- Can be used to build gravity walls up to 3 feet high, including buried bed course, but excluding the cap.* Taller walls can be built using geosynthetic reinforcement or the Anchorplex™ retaining wall system when designed by a qualified engineer.
- Minimum outside radius, measured on the top course to the front of the units: 4 feet**
- Minimum inside radius, measured on the base course to the front of the units: 8 feet**
- Setback/System Batter 1"/ 9.5 degrees

*The maximum gravity wall height is project specific and may be lower than this height.

**May vary depending on the installation pattern.