



# DIAMOND PRO PS

## RETAINING WALL SYSTEM STONE CUT

A RICH FACETED APPEARANCE  
 NOT FOUND IN COMMON  
 COMMERCIAL WALLS

### ☑ FEATURES & BENEFITS

- This pinned version of the legendary DIAMOND PRO® block presents the option of 7° or Near Vertical installation. Additional system batter can be created by alternating pin placement on each course of wall.
- Build walls in excess of 50 feet when combined with geosynthetic reinforcement†
- ASTM C1372 – compliant
- Large cores for ease of handling and drainage aggregate placement during installation.
- Supported by Anchorwall® design software and estimating tools
- Compatible fittings/accessories

<sup>†</sup>See Installation Guide. Reinforced walls, and other critical walls, must be designed by qualified engineers.  
<sup>‡</sup>Dimensions and Weights may differ by face style and by manufacturer.  
<sup>§</sup>Gravity wall heights are based on project specific conditions and may be less than this value.  
<sup>¶</sup>Measured on the top course to the front of the wall.  
<sup>\*\*</sup>Measured on the base course to the front of the wall.

<b>H X W X D*</b>	8" X 18" X 12****
<b>WEIGHT*</b>	76 LBS.
<b>COVERAGE</b>	1 SQ. FT.
<b>SETBACK &amp; BATTER</b>	1" PER COURSE (7.1°) OR NEAR VERTICAL
<b>MAX. GRAVITY WALL HT.**</b>	4 FT.
<b>MIN. OUTSIDE RADIUS†</b>	4 FT.
<b>MIN. INSIDE RADIUS††</b>	6 FT.