



DEVELOPED BY
ANCHOR
DIAMOND
WALL INDUSTRY EXPERTS



DIAMOND PRO[®] PS

RETAINING WALL
SMOOTH FACE

A REFINED MODERN APPEARANCE
WITH TIME-TESTED STRENGTH

✔ FEATURES & BENEFITS

- This pinned version of the legendary DIAMOND PRO[®] block presents the option of 7° or Near Vertical installation. Additional system batter can be created by alternating pin placement on each course of wall.
- Build walls in excess of 50 feet when combined with geosynthetic reinforcement†
- ASTM C1372 – compliant
- Large cores for ease of handling and drainage aggregate placement during installation.
- Supported by Anchorwall[®] design software and estimating tools
- Anchor Sculpsit[®] molded face finish
- Compatible fittings/accessories

H X W X D*	8" X 18" X 12"
WEIGHT*	75 LBS.
COVERAGE	1 SQ. FT.
SETBACK & BATTER	1" PER COURSE (7.1°) OR NEAR VERTICAL
MAX. GRAVITY WALL HT.**	4 FT.
MIN. OUTSIDE RADIUS†	4 FT.
MIN. INSIDE RADIUS††	6 FT.

*See Installation Guide. Reinforced walls, and other critical walls, must be designed by qualified engineers.

†Dimensions and Weights may differ slightly from manufacturer to manufacturer.

**Gravity Wall heights are based on project specific conditions and may be lower than this value.

†Measured on the top course to the front of the wall.

††Measured on the base course to the front of the wall.



ANCHOR DIAMOND Group
5909 Baker Rd. Suite 550
Minnetonka, MN 55345
☎ 1-952-933-8855

For more info visit
anchordiamond.com



©2023 ANCHOR DIAMOND Group. All rights reserved.
AD23-001-DIAMOND PRO PS SMOOTH FACE