



VERTICA PRO[®]

RETAINING WALL
 BEVELED FACE

USED IN COMMERCIAL SITE
 DEVELOPMENT AND ANYWHERE
 SPACE IS AT A PREMIUM

✔ FEATURES & BENEFITS

- ASTM C1372 – compliant
- ICC evaluated
- Walls in excess of 60 feet high have been built with the Vertica system when combined with geosynthetic reinforcement++
- Supported by Anchorwall[®] design software and estimating tools
- Integral locating features – available in two setback/batter configurations (2° and 4°)
- Compatible fittings / accessories.



¹See Installation Guide. Reinforced walls, and other critical walls, must be designed by qualified engineers.
²Dimensions and Weights may differ slightly from manufacturer to manufacturer.
³Gravity wall heights are based on project specific conditions and may be lower than this value.
⁴Measured on the top course to the front of the wall.
⁵Measured on the base course to the front of the wall.

H X W X D¹	8" X 18" X 20"
WEIGHT²	112 LBS.
COVERAGE	1 SQ. FT.
SETBACK (PER COURSE); BATTER	9/32"; 2° OR 9/16"; 4°
MAX. GRAVITY WALL HT.³	6 FT.
MIN. OUTSIDE RADIUS⁴	6 FT.
MIN. INSIDE RADIUS⁵	8 FT.