



FREESTANDING WALL

THE ELEGANT NATURAL STONE LOOK PROVIDES REMARKABLE VERSATILY FOR OUTDOOR PROJECTS



LARGE WALL UNIT	Dimensions* H x W x D (in)	Weight* (lbs)	Coverage (sqft)
TAY.	6 x 16 x 5	28	0.67
MEDIUM WALL UNIT	Dimensions* H x W x D (in)	Weight* (lbs)	Coverage (sqft)
1 3	6 x 10 x 5	19	0.42
SMALL WALL UNIT	Dimensions* H x W x D (in)	Weight* (lbs)	Coverage (sqft)
	6 x 6 x 5	11	0.25
CORNER/ COLUMN	Dimensions* H x W x D (in)	Weight* (lbs)	Coverage (linft)
No.	6 x 16 <sup>3</sup> / <sub>4</sub> x 8	57	
WALL END	Dimensions* H x W x D (in)	Weight* (lbs)	Coverage (linft)
164/1	6 x 8 x 11	36	
CAP END	Dimensions* H x W x D (in)	Weight* (lbs)	Coverage (linft)
Danger	$3 \times 8 \times 13^{1}/_{2}$	21	0.67
DOUBLE SIDED CAP	Dimensions* H x W x D (in)	Weight* (lbs)	Coverage (linft)
35	$3 \times 8/7 \times 13^{1}/_{2}$	22	0.63
TORPEDO™ BASE BLOCK	Dimensions* H x W x D (in)	Weight* (lbs)	Coverage (linft)
0	4 x 15 <sup>3</sup> / <sub>4</sub> x 11	47	1.31



## **⊘** FEATURES & BENEFITS

- Can be used to build walls up to 3 feet high, including buried course, but excluding the cap.
- Minimum radius using all three units: 4 feet.\*

\*May vary depending on the installation pattern.







