

PRODUCT QUANTITY ESTIMATOR

To use: 1. Locate wall length to determine number of Torpedo[™] base blocks needed. 2. Combine wall length and exposed wall height to determine number of wall blocks needed. The Belair® freestanding wall system can be used to build walls up to 3 feet including base course, but excluding the cap.* Installation instructions and estimating are based on using sets.

3. Add double-sided cap block quantities.

	Buried Base Blocks	Exposed Wall Block Set = 2 Finished SF; 1 Face Ft.	Cap Blocks
System Blocks	Torpedo™ base block 4" x 15¾" x 11"	The 6-inch-high block set consists of two 6" x 16" blocks and one each of the 6" x 10" and 6 x 6" blocks.	Double-Sided 3" x 8"/7" x 13½" Cap End 3" x 8" x 13½"

1. BASE BLOCK QUANTITIES

		Wall Length										
		5'	10'	15'	20'	25'	30'	35'	40'	45'	50'	
Belair® 6" wall blocks	Number of Sets	2	3	4	5	7	8	9	10	12	13	
Torpedo™ base block*	Number of Blocks	4	8	12	16	20	23	27	31	35	39	

2. EXPOSED WALL BLOCK QUANTITIES

Exposed		Wall Length									
Wall Height		5'	10'	15'	20'	25'	30'	35'	40'	45'	50'
1'0"	Number of Sets	3	5	8	11	13	15	18	20	23	25
1'6"		4	8	12	15	19	23	27	30	34	38
2'0"		6	10	15	20	25	30	35	40	45	50
2'6"		7	13	19	25	32	38	44	50	57	63

3. DOUBLE-SIDED CAP BLOCK QUANTITIES (exclude a cap if ending with a cap end)

		Wall Length									
Wall Type	Wall Type		10'	15'	20'	25'	30'	35'	40'	45'	50'
Straight	Number of Blocks	9	17	25	33	41	49	57	65	73	81
Curved		10	19	28	37	46	54	63	72	81	90

^{*}The Torpedo™ base block is available in select markets, and can be used for retaining walls featuring the Anchor rear-lip design up to the retaining wall system's gravity wall height.

© 2022 ANCHOR Diamond® retaining wall systems are manufactured under license from ANCHOR Diamond®. The wall system blocks are covered by the Anchor Diamond® Limited Warranty. For a complete copy, visit your local dealer or see anchordiamond.com. All rights reserved.

Anchor Diamond® 5909 Baker Rd. Suite 550 • Minnetonka, I 4WS22-253 10/22

^{**} This height assumes level backfill and clean, compacted sand or gravel and no surcharge. Taller walls can be built with the system blocks as the buried base course and geosynthetic reinforcement, or with the Anchorplex™ retaining wall system, when designed by a qualified engineer.