



PLACE GEOGRID REINFORCEMENT SUCH THAT ITS ALIGNMENT IS PERPENDICULAR TO FACE OF WALL AND THAT 100% COVERAGE OF REINFORCED FILL IS PROVIDED.

NOTES:

- 1. ALTERNATE COURSES "A" & "B" AS NEEDED TO FULL HEIGHT OF WALL.
- 2. MODIFY UNITS AS NEEDED TO MAINTAIN RUNNING BOND.
- 3. ADHERE ALL PARTIAL UNITS WITH CONSTRUCTION GRADE ADHESIVE.
- 4. ADJUST PLACEMENT IN FIELD TO ACHIEVE DESIRED ANGLE
- 5. FREE-DRAINING AGGREGATE (NOT SHOWN) TO SPAN 10 FT. ALONG THE WALL FACE AND TO THE BACK OF THE REINFORCED ZONE



© 2017 Anchor Wall Engineering, LLC ® and ™ Anchor Wall Systems, Inc. www.anchorwall.com This drawing is for illustrative purposes only and should not be used for construction without the signature of a registered professional engineer. Sterling™ Retaining Wall System
Outside Angles

	Scale:	Drawn by:
	3/8" = 1'-0"	SB
	Date:	Drawing number
	10/11/2017	SRST31