

Stepping Up the Base

MULTIPIECE SYSTEM INSTALLATION GUIDELINES

Walls built on a sloping grade must always be constructed with leveled, horizontal courses. Courses should not be sloped to match the slope of the surrounding ground levels. Walls built on a sloping grade require a stepped base (footing or leveling pad) which steps up the slope in 6-inch increments as often as required.


LOWEST POINT

Begin excavation at the lowest point and dig a level trench into the slope until it is deep enough to accommodate the base material and one entire block. Form the base and lay the first course of blocks starting at the bottom of the slope, working upwards.

STEP UP

At this point, step up the height of one block and begin a new section of base trench. Once compacted, the base must be exactly level with the top of the course of blocks previously installed. At each step-up point, the trench should also step back towards the rear of the wall to allow for the setback of each new base course and to ensure the wall remains centered on the leveling pad as it progresses up the slope.

Continue to step up as needed to top of slope. Always bury at least one full unit at each step.



© 2011 Anchor Wall Systems, Inc. Anchor™ retaining wall systems are manufactured under license from Anchor Wall Systems, Inc. (AWS). The "Anchor Build Something Beautiful" logo is a trademark of AWS. The wall system blocks are covered by the AWS Limited Warranty. For a complete copy, visit your local dealer or see anchorwall.com. All rights reserved.

Anchor Wall Systems, Inc., 5959 Baker Road, Suite 390, Minnetonka, MN 55345.
A&B0925 - 4023

WMP926 04/11