








STRAIGHT RUN



OUTSIDE CURVE

- . CAREFULLY CUT ALONG LINE TO PRESERVE BOTH SIDES OF THE CUT
- 2. FLIP PIECES "B" AND "D" OVER TO CREATE CORNER





WALL FACE

NOTES:

- 1. ALWAYS START CAPPING WALL FROM THE LOWEST ELEVATION.
- 2. LAY OUT CAPS PRIOR TO USING ADHESIVE.
- 3. CUT CAPS TO FIT. OCCASIONAL CUTTING WILL BE NECESSARY FOR RADII OTHER THAN APPROXIMATELY 7.5 FEET.
- ALTERNATE SHORT AND LONG CAP FACES EVERY OTHER CAP TO ACHIEVE A STRAIGHT ROW OF CAPS.
- 5. USE EXTERIOR-GRADE CONSTRUCTION ADHESIVE TO SECURE CAPS.
- 6. * INDICATES CAP END UNIT



Anchor Wall Systems, Inc. 5959 Baker Road, Suite 390 Minnetonka, MN 55345

© 2013 Anchor Wall Systems, Inc. ® and TM Anchor Wall Systems, Inc.

Drawn By: SB	Brisa [®] 6" and Brisa [®] Random Retaining Wall Systems
Date: 5/13/2013	Capping Details
Scale: 3/8"=1'-0"	Typical Details For Segmental Retaining Walls