

DIAMOND PRO PS

RETAINING WALL BEVELED FACE

FLEXIBLE COST-EFFECTIVE SOLUTION FOR LARGE WALLS WITH A MULTI-DIMENSIONAL LOOK

OFEATURES & BENEFITS

- This pinned version of the legendary DIAMOND PRO® block presents the option of 7° or Near Vertical installation. Additional system batter can be created by alternating pin placement on each course of wall.
- Build walls in excess of 50 feet when combined with geosynthetic reinforcement†
- ASTM C1372 compliant
- Large cores for ease of handling and drainage aggregate placement during
- Supported by Anchorwall® design software and estimating tools
- Compatible fittings/accessories

See Installation Guide.

†Reinforced walls, and other critical walls, must be designed by qualified engineers.

Dimensions and Weights may differ slightly from manufacturer to manufacturer.

"The maximum gravity wall height is based on project specific conditions and may be lower than this value.

†Measured on the top course to the front of the wall.

#Measured on the base course to the front of the wall.

HXWXD. WEIGHT. COVERAGE **SETBACK & BATTER**

77 LBS. 1 SQ. FT.

MAX. GRAVITY WALL HT." MIN. OUTSIDE RADIUS† MIN. INSIDE RADIUS†† 1" PER COURSE (7.1°) OR NEAR VERTICAL

8" X 18" X 12""

4 FT. 4 FT. 6 FT.



